

Kodak

i30 and i40 Scanners



Get everything you want from a small desktop scanner—and more.

Kodak i30 and i40 Scanners offer easy setup and integration, fast scanning speed and a USB 2.0 interface for quick image transfer. Plus you get great image quality with Perfect Page Scanning, a Kodak exclusive.

You want fast

- Scan up to 25 pages—or 50 images—per minute
- Select up to nine assigned scanning applications (such as **Kodak Capture Software**) at the touch of a button
- Automatic image cropping and straightening means outstanding image accuracy at full scanning speed

You want easy

- Easy to use and fit in any work space
- A unique special document feeder on the i40 model allows front-feed, front-return scanning of small documents such as driver's licenses and insurance cards
- Flexible Electronic Color Dropout automatically suppresses non-critical red, green or blue background to improve forms processing
- Reliable multi-feed detection for better scanning productivity
- VRS compatible for more imaging options

You want great images

- Get renowned image quality from Perfect Page Scanning— advanced image processing that allows you to scan even poor-quality documents at full speed and get exceptional images

- Five output options let you choose between color, bitonal, grayscale, simultaneous bitonal and grayscale, and simultaneous bitonal and color
- Customize color output to fit your application

Kodak Service & Support

Our team of service experts is here for you around the clock and around the world.



Kodak i30 and i40 Scanners

Recommended Daily Volume	Up to 1,000 pages per day
Throughput Speeds (portrait, letter size)	Bitonal/grayscale: Up to 25 ppm/50 ipm at 200 dpi Color: Up to 25 ppm/50 ipm at 150 dpi; up to 25 ppm/40 ipm at 200 dpi
Scanning Technology	i30: Single CCD; i40: Dual CCD; Grayscale output bit depth is 256 levels (8-bit) Color capture bit depth is 48 bits (16 x 3); Color output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi
Illumination	Fluorescent (cold cathode)
Output Resolution	75, 100, 150, 200, 240, 300, 400 and 600 dpi
Maximum Document Size	215 mm x 863 mm (8.5 in. x 34 in.)
Minimum Document Size	Single-sheet feeding: 50 mm x 87.5 mm (2.0 in. x 3.5 in.) Multiple-sheet feeding: 87.5 mm x 125 mm (3.5 in. x 5.0 in.)
Paper Thickness and Weight	ADF: 52-105 g/m ² (14-28 lb.) paper Special document feeder (i40 Scanner only): Handles documents up to 1 mm (0.04 in.) thick
Feeders	ADF: Up to 50 sheets of 75 g/m ² (20 lb.) paper Special document feeder (i40 Scanner only): Allows front-feed, front-return single document scanning
Multi-Feed Detection	Length detection
Connectivity	USB 2.0
Bundled Software	TWAIN and ISIS drivers; Kodak Capture Software, Lite; Readiris Pro Corporate Edition
Imaging Features (in the scanner)	Perfect Page Scanning, adaptive threshold processing, deskew, autocrop, relative cropping, aggressive cropping, electronic color dropout, simultaneous output of bitonal and color or bitonal and grayscale images, color processing tables, image edge fill, blank page removal
File Format Outputs	BMP, TIFF and JPEG (searchable PDF with bundled software)
Warranty (US and Canada)	One-year warranty
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	i30 Standby: <12 Watts; i30 Running: <30 Watts; i40 Standby: <12 Watts; i40 Running: <40 Watts
Environmental Factors	Energy Star qualified scanners; Operating temperature: 10-35° C (50-95° F) Operating humidity: 10% to 85% RH
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <46 dB(A) Operating mode: <58 dB(A)
Recommended PC Configuration	For documents up to 356 mm (14 in.) at 400 dpi: Pentium IV , 2.5 GHz processor, 512 MB RAM For documents up to 660 mm (26 in.) at 400 dpi: Pentium IV , 2.5 GHz processor, 1 GB RAM For longer documents/higher resolutions: Pentium IV , 2.5 GHz processor, 3 GB RAM
Supported Operating Systems	Windows XP (supports USB 2.0), Windows 2000 Professional (supports USB 2.0) Windows Me (USB 1.1 support only), Windows 98SE (USB 1.1 support only)
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 Class B, VCCI (Class B), CNS 13438 (Class B), (BSMI Mark), UL 60950 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed Module, Roller Cleaning Pads, Staticide Wipes
Dimensions	Weight i30: 3.6 kg (7.9 lbs.) i40: 4.1 kg (9.0 lbs.) Depth: 168 mm (6.6 in.) (not including trays) Width: 337 mm (13.2 in.) Height: 162 mm (6.4 in.) (not including input tray)

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.



As an **Energy Star**® Partner, Eastman Kodak Company has determined that these products meet **Energy Star**® guidelines for energy efficiency.

For more information visit: www.kodak.com/go/docimaging

Eastman Kodak Company, Document Imaging, Rochester, NY 14650 1-800-944-6171
Kodak Canada, Inc., Toronto, Ontario M6M 1V3 1-800-465-6325
Kodak GmbH Hedelfingerstr 60, 70327 Stuttgart, Germany EAMER-DI-Capture@kodak.com
Kodak (Australasia) Pty. Ltd. North Ryde NSW 2113 Australia 61-2-9870-4224
Kodak (Hong Kong) Limited North Point, Hong Kong 07021 852-2654-9330
Kodak Japan Limited, Tokyo, Japan 81-3-5540-2270 jp-di-mktg@kodak.com
Kodak de Mexico Mariano Otero 408 Guadalajara, Mexico (52) (33) 3818-6598
For other areas outside the U.S.A., call +1-585-722-9287



Innovation you can count on™

© Kodak, 2006. Kodak is a trademark.

A-5730 CAT No. 812 7359 Printed in USA 04/06

Kodak